Appendix K - Self-Evaluation Results - Park Facilities

A comprehensive overview of all public areas in City of Grand Rapids facilities was performed in 2019. The results of the evaluations are shown in the appendix below.

		essii Route			arkin Stalls	-		urfac arkin			arkin Signs	٠	Cur	b Raı	mps		Play	ent	Pa	vilio	n	Be	ench	es	1	Гable	s
											Ť		-		Ė		Ė										
Park Name	Compliant	Noncompliant	Not Applicable	Compliant	Noncompliant	Not Applicable	Compliant	Noncompliant	Not Applicable	Compliant	Noncompliant	Not Applicable	Compliant	Noncompliant	Not Applicable	Compliant	Noncompliant	Not Applicable	Compliant	Noncompliant	Not Applicable	Compliant	Noncompliant	Not Applicable	Compliant	Noncompliant	Not Applicable
American Legion Memorial Park			Х			Х			Х			Х			Х			Х	Х			Х			Х		
Angel of Hope		X			X			X			X		Х					Х			Х		X			X	
Blandin Beach	Х				X			X			Х			Х		Х					Х	х			х		
Central School	Х			Х			Х				X			Х				Х			Х	Х				X	
Crystal Lake	Х				X			X			Х		Х			Х			Х			Х			Х		
Grussendorf Park	х				Х			X			Х			Х			X				Х	х			х		
Hale Lake Landing			Х			Х			Х			Х			Х			Х			Х			Х	Х		
Hillside Park			Х			Х			Х			Х			Х			Х			Х			Х			Х
Isaac Walton Landing			Х			Х			Х			Х			Х			Х			Х			Х			Х
Lost Creek Park		Х			X			X			Х			X		Х					Х	х			х		
Maplewood Park		X			X			X			X				Х	Х					Х	х			х		
McGowans Park		Х			X			X			Х			X				Х			Х	Х			х		
McKinney Lake Landing			Х			Х			Х			Х			Х			Х			Х			Х			Х
Newtons Sliding Hill		X			X			X			X				Х			Х			Х			Х		X	
Oakland Park	Х				X			X			X		Х			Х					Х	Х			х		
Pokegama Park Place	Х			Х			Х			Х			Х					Х			Х		Х			X	
River Front Trail	Х			Х			Х				Х				Х			Х			Х	х			х		
Skogebo Park			Х			Х			Х			Х			Х			Х			Х			Х			Х
Sports Complex			Х			Х			Х			Х			Х			Х			Х			Х			Х
Steamboat Landing	Х				X			X			X				Х			Х			Х			Х			Х
Sylvan Landing	Х				X			X			X		Х					Х			Х	Х			Х		
Sylvan Point Trails	Х				X			X			X				Х			Х			Х			Х			Х
Veterans Memorial Park		X			X			X			X				Х			Х			Х	Х			Х		
Wilcox Park		Х			X			Х			Х				Х			Х			Х			Х		Х	
Willow Park		Х			Х			Х			Х				х	Х					Х			Х	х		

Building: American Legion Park	
Location:	
Date: 10/8/19	
Evaluated By: Dom DeGuiseppi	

Priority 5	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design — 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	Gravel, grass, and street
	number of accessible	Total #:	1 - 25	1	parking
	spaces provided?	Accessible #:	26 - 50	2	Parrang
	[208.2]		51 - 75	3	
			76 - 100	4	
			100+ see 2010 St	tandards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: NA		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Accessible Route			
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No		
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: NA	36"min	
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		424"max + 48"min - 24"max + 32"min 32"min	
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min	
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max	

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: NA		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: NA		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 8%	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: 1.3%		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: 90" Yes No Measurement: 70" Yes No Yes No Measurement: 17"	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible? Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No Total #: 5 Accessible #: 2 Yes No		

Evaluated By: Dom DeGuiseppi	
Date: 10/1/19	
Location: SE 1st Street	
Building: Angel of Hope	

Priority	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	Street parking
	number of accessible	Total #:	1 - 25	1	
	spaces provided?	Accessible #:	26 - 50	2	
	[208.2]		51 - 75	3	
			76 - 100	4	
			100+ see 2010 S	tandards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: NA		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	■ Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: 8'	36"min		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		48"min — 24"max - 32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 6.4%	
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: 3%	
Curb	Ramps Yes No		
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No	
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement: 7.9%	1 1 2 min 1
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement: 1.2%	48 min 1

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement: 48"	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	No landing
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No Measurement:	→ 10 min — 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	12 min 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be approached and exited at			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: 14.5" Yes No Measurement: 14.6" Yes No Measurement: 16"	48" min 30" min 20"- 24" min 17"- 19"	One bench does not have back support Two hanging benches
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible? Is/are the accessible space(s) distributed throughout the	Yes No Total #: 1 Accessible #: 0 Yes No		
		Yes No		

Building: Blandin Beach	
Location: NW 10th Ave	
Date: 10/8/19	
Evaluated By: Dom DeGuiseppi	

Priority 5	Priority 5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design — 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	
	number of accessible spaces provided? [208.2]	Total #: 26 Accessible #:	1 - 25	1	
			26 - 50	2	
		1	51 - 75	3	
			76 - 100	4	
			100+ see 2010 St	andards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement: 10'			No painted aisle Parking space is wide enough

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: 3.5%		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement: 85"	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	■ Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: 46"	36"min		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		424"max + 48"min - 24"max + 32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 1.5%		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: 1.1%		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement: 6.5%	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement: 1.1%	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement: 48"	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No Measurement:	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavilio	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 2.2%	

Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: 1.1%		
es Yes No			
Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: 70" Yes No Yes No Measurement: 17"	48" min 30" min 20"- 24" min 17"- 19"	
Tables Yes No			
Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible? Is/are the accessible space(s) distributed throughout the facility and located on an	Yes No Total #: 5 Accessible #: 1 Yes No		
	es Yes No Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903] Tables Yes No Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	## Measurement: 1.1%	1:48? [403.3] Measurement: 1.1% Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903] Tables Yes No Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible? Is/are the accessible space(s) distributed throughout the facility and located on an

Building: Central School				
Location:				
Date: 10/9/19				
Evaluated By: Dom DeGuiseppi				

Priority	5 - Parks			
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:		
Parking	Yes No			
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces
	number of accessible	Total #: 48	1 - 25	1
	spaces provided?	Accessible #:	26 - 50	2
	[208.2]	2	51 - 75	3
			76 - 100	4
			100+ see 2010 St	tandards 208.2
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement: 8'		

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: 2.3%		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	One sign height is to short
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route					
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No				
5.10	Is the route at least 36 inches wide? [403.5.1] Note: The accessible route can narrow to 32 inches	Yes No Measurement: 8'	36"min 48"min 24"max + 32"min 32"min	Sidewalk around Central school is 8' wide		
	min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.					
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min			
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max			

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 4.8%	
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:	
Curb I	Ramps Yes No		
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No	
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement: 2.5%	12 min 1
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement: .8%	48 min 1

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement: 36"	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4] If there are curb ramp flares, are	Yes No Measurement:	36"min	No Landing
	the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Measurement:	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:	THE STATE OF THE S	
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: 70" Yes No Yes No Measurement: 17"	48" min 30" min 20"- 24" 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 3 Accessible #: 0		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes ■ No		

Building: Crystal Lake Park				
Location:				
Date: 10/8/19				
Evaluated By: Dom DeGuiseppi				

Priority !	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate number of accessible spaces provided? [208.2]	Yes No Total #: Accessible #:	1 - 25 26 - 50 51 - 75 76 - 100 100+ see 2010 St	Accessible Spaces 1 2 3 4 andards 208.2	Street side parking
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			No markings

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: NA		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	■ Yes No		
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: 6'	36"min	
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		48"min — 24"max - 32"min 32"min	
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min	
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max	

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 1.4%	
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: .9%	
Curb I	Ramps Yes No		
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No	
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement: 7.9%	12 min 1
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement: .2%	48 min 1

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement: 36"	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4] If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run?	Yes No Measurement: .6% Yes No Measurement:	36"min	
5.20	[406.3] If the landing at the top is less than 36 inches long, are there curb ramp flares? Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Yes No Measurement:	1 12 min 1	
Acces	Accessible Play Components Yes No			
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes ■No Yes ■No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavilio	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 3.3%	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: .4%		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: 118" Yes No Measurement: 70" Yes No Measurement: 17"	48" min 30" min 20"- 24" 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible? Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No Total #: 3 Accessible #: 1 Yes No		

Evaluated By: Dom DeGuiseppi	
Date: 10/2/19	
Location: 7th Ave SW	
Building: Grussendorf	

Priority	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	Street side
	number of accessible spaces provided? [208.2]	Total #: 24	1 - 25	1	parking is available
		Accessible #:	26 - 50	2	- available
		0	51 - 75	3	-
			76 - 100	4	-
			100+ see 2010 St	tandards 208.2	-
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Accessible Route			
5.9	Is the route stable, firm and slip-resistant? [302.1]	■ Yes No		
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: 48"	36"min	
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		48"min — 24"max — 32"min 32"min	
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min	No passing space
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max	

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 1.2%	
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: 1.5%	
Curb I	Ramps Yes No		
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No	
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement: 7.2%	12 min 1
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement: 2.6%	48 min 1

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement: 36"	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4] If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run?	Yes No Measurement: 2.8% Yes No Measurement:	36"min	
	[406.3]			
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	12 min 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		Accessible equipment but playground has curb surrounding it without ramps
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			nt without ramps

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route	Yes No	
	to the components?	Yes ■ No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface?	Yes No	
	Note: Objects below 80 inches may not protrude into the accessible route.		
Pavilio	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3]	Yes No Measurement:	
	Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.		

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: 70" Yes No No Measurement: 17"	48" min 30" min 20"- 24" min 17"- 19"	Ground
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 2 Accessible #: 2		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Hale Lake Landing	
Location:	
Date: 10/8/19	
Evaluated By: Dom DeGuiseppi	

Priority 5	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	No marked spaces
	number of accessible	Total #:	1 - 25	1	spaces
	spaces provided?	Accessible #:	26 - 50	2	
	[208.2]		51 - 75	3	
			76 - 100	4	
			100+ see 2010 St	andards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement:	36"min 48"min 48"max		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:			
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:			
Curb F	Curb Ramps Yes No				
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No			
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1		
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1		

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:				
Bench	Benches Yes ■No					
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" 17"- 19"			
Dining	Tables Yes No					
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible? Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No Total #: 2 Accessible #: 1 Yes No				

Building: Hillside Park	
Location: Forest Hills Avenue	
Date: 10/1/19	
Evaluated By: Dom DeGuiseppi	

Priority 5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:		
Parking	Yes No			
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces
	number of accessible	Total #:	1 - 25	1
	spaces provided?	Accessible #:	26 - 50	2
	[208.2]		51 - 75	3
			76 - 100	4
			100+ see 2010 St	tandards 208.2
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:		

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement:	36"min 48"min 48"max		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:			
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:			
Curb F	Curb Ramps Yes No				
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No			
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1		
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1		

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No	I		
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: Accessible #:		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Isaac Walton Landing
Location: County Road 63
Date: 10/2/19
Evaluated By: Dom DeGuiseppi

Priority 5 - Parks					
Priority 5) - Parks				T
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	Dirt lot
	number of accessible	Total #:	1 - 25	1	
	spaces provided?	Accessible #:	26 - 50	2	
	[208.2]		51 - 75	3	
			76 - 100	4	
			100+ see 2010 St	andards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: NA		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route					
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No				
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement:	36"min 48"min 48"max			
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min			
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min			
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max			

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No	I		
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: Accessible #:		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Lost Creek Park	
Location: NW 4th Ave	
Date: 10/8/19	
Evaluated By: Dom DeGuiseppi	

Priority 5	riority 5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	Street Parking
	number of accessible	Total #:	1 - 25	1	
	spaces provided?	Accessible #:	26 - 50	2	
	[208.2]		51 - 75	3	
			76 - 100	4	
			100+ see 2010 St	andards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No		
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement:	36"min 48"min 48"max	
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min	
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min	
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max	

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 1 min 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.			
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route	Yes No		
	to the components?	Yes ■No		
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface?	Yes No		
	Note: Objects below 80 inches may not protrude into the accessible route.			
Pavilion Yes No				
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No		
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No		
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3]	Yes No Measurement:		
	Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.			

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: 70" Yes No Yes No Measurement: 17"	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 3 Accessible #:		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Maplewood Park
Location: SE 4th Ave and SE 14th Street
Date: 10/1/19
Evaluated By: Dom DeGuiseppi

Priority 5	Priority 5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	Dirt lot, no
	number of accessible	Total #: 5	1 - 25	1	markings except for railroad ties
	spaces provided?	Accessible #:	26 - 50	2	Tor ramoud tioo
	[208.2]	0	51 - 75	3	
			76 - 100	4	
			100+ see 2010 St	tandards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			Not marked

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: 5.8%		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Accessible Route			
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No		
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement:	36"min 48"min 48"max	
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min	
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min	
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max	

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 1 min 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components?	Yes No	
	If so, is there an accessible route to the components?	Yes ■No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface?	Yes No	
	Note: Objects below 80 inches may not protrude into the accessible route.		
Pavilio	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3]	Yes No Measurement:	
	Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.		

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: 70" Yes No No Measurement: 17"	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 4 Accessible #: 1		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: McGowan Park	
Location:	
Date: 10/2/19	
Evaluated By: Dom DeGuiseppi	

Priority 5	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate number of accessible spaces provided? [208.2]	Yes No Total #: Accessible #:	1 - 25 26 - 50 51 - 75 76 - 100 100+ see 2010 St	Accessible Spaces 1 2 3 4 andards 208.2	Street Parking
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: NA		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: NA	36"min		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		424"max + 48"min - 24"max + 32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: NA		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: NA		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement: NA	1 12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement: NA	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement: 44"	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4] If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No Measurement: NA Yes No Measurement: NA	36"min	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares? Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Yes No Measurement:	1 1 min 1	
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route	Yes No	
	to the components?	Yes ■ No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface?	Yes No	
	Note: Objects below 80 inches may not protrude into the accessible route.		
Pavilio	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3]	Yes No Measurement:	
	Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.		

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: 68" Yes No Yes No Measurement: 19"	48" min 30" min 20"- 24" min 17"- 19"	Ground
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible? Is/are the accessible space(s)	Yes No Total #: 2 Accessible #: 1		
	distributed throughout the facility and located on an accessible route?	Yes No		

Building: McKinney Lake Landing
Location:
Date: 10/8/19
Evaluated By: Dom DeGuiseppi

Priority	Priority 5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate number of accessible spaces provided? [208.2]	Yes No Total #: Accessible #:	Total Spaces 1 - 25 26 - 50 51 - 75 76 - 100 100+ see 2010 See	Accessible Spaces 1 2 3 4 tandards 208.2	Gravel Lot
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement:	36"min 48"min 48"max		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No	I		
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: Accessible #:		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Newtons Sliding Hill	
Location:	
Date: 10/8/19	
Evaluated By: Dom DeGuiseppi	

Priority !	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate number of accessible spaces provided? [208.2]	Yes No Total #: Accessible #:	1 - 25 26 - 50 51 - 75 76 - 100 100+ see 2010 St	Accessible Spaces 1 2 3 4 andards 208.2	Grass and gravel
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement:	36"min 48"min 48"max		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No		1	
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: Accessible #:		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Oakland Park	
Location: SE 4th Street	
Date: 10/2/19	
Evaluated By: Dom DeGuiseppi	

Priority 5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:		
Parking	Yes No			
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces
	number of accessible	Total #: 22	1 - 25	1
	spaces provided?	Accessible #:	26 - 50	2
	[208.2]	0	51 - 75	3
			76 - 100	4
			100+ see 2010 St	tandards 208.2
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:		

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: NA		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	■ Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: 10'	36"min		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 2.4%		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: 1%		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement: 2.2%	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement: .7%	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement: 12'	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4] If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are	Yes No Measurement: 2.8% Yes No Measurement:	36"min	
	at least 10 inches of flare run? [406.3]			
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares? Are the slopes of the flares no	Yes ■ No	12 min 1	
	greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route	Yes No	
	to the components?	Yes ■No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface?	Yes No	
	Note: Objects below 80 inches may not protrude into the accessible route.		
Pavilio	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3]	Yes No Measurement:	
	Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.		

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: 70" Yes No Yes No Measurement: 18"	48" min 30" min 20"- 24" min 17"- 19"	Ground
5.28	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 2 Accessible #:		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Pokegama Golf Course	
Location: Golf Course Road	
Date: 10/2/19	
Evaluated By: Dom DeGuiseppi	

Priority 5 - Parks					
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			Sidewalk from parking lot to building
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate number of accessible spaces provided? [208.2]	Yes No	Total Spaces	Accessible Spaces	
		Total #: Accessible #: 5	1 - 25	1	
			26 - 50	2	
			51 - 75	3	
			76 - 100	4	
			100+ see 2010 Standards 208.2		
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement: 7.5'			Shape of spaces creates uneven spaces

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: 2.3		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement: 58"-63"	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	■ Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: 10'	36"min		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 6.3%	
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: 2.4%	
Curb F	Ramps Yes No		
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No	
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement: 5.4%	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement: 1.4%	48 min 1

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement: 10'	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4] If there are curb ramp flares, are	Yes No Measurement:	36"min	No landing
	the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Measurement:	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	12 min 1	No landing
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:	THE CONTRACTOR OF THE CONTRACT	
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components?	Yes No	
	If so, is there an accessible route to the components?	YesNo	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface?	Yes No	
	Note: Objects below 80 inches may not protrude into the accessible route.		
Pavilio	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3]	Yes No Measurement: 6.3%	
	Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.		

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: 1.2%		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" 42" min 17"- 19"	
			17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 2 Accessible #: 0		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: River Front Trail
Location: Library
Date: 10/8/19
Evaluated By: Dom DeGuiseppi

Priority	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate number of accessible spaces provided?	Yes No	Total Spaces 1 - 25	Accessible Spaces	-
	[208.2]	Accessible #: 5	26 - 50 51 - 75 76 - 100	2 3 4	-
			100+ see 2010 S	tandards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement: 5'			One access aisle is not marked and one is less than 8'

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement: 84"	60"min	One sign is to 84" tall
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No		
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: 8'	36"min	
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		48"min — 24"max > 32"min 32"min	
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min	
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max	

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: .4%		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: .3%		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Measurement: 72" Yes No Measurement: 70" Yes No Measurement: No Measurement: 17"	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 3 Accessible #: 1		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Skogebo Park	
Location: SW 1st Street	
Date: 10/1/19	
Evaluated By: Dom DeGuiseppi	

Priority 5	Priority 5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	No lot/street
	number of accessible	Total #:	1 - 25	1	parking only
	spaces provided?	Accessible #:	26 - 50	2	
	[208.2]		51 - 75	3	
			76 - 100	4	
			100+ see 2010 St	andards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Accessible Route			
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No		
5.10	Is the route at least 36 inches wide? [403.5.1] Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.	Yes No Measurement:	36"min 48"min 24"max 32"min 32"min	
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min	
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max	

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:			
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:			
Curb F	Curb Ramps Yes No				
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No			
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1		
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1		

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No	I		
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: Accessible #:		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Sports Complex	
Location:	
Date: 10/10/19	
Evaluated By: Dom DeGuiseppi	

Priority !	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			Under construction
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	
	number of accessible	Total #:	1 - 25	1	
	spaces provided?	Accessible #:	26 - 50	2	
	[208.2]		51 - 75	3	
			76 - 100	4	
			100+ see 2010 S	tandards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route					
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No				
5.10	Is the route at least 36 inches wide? [403.5.1] Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.	Yes No Measurement:	36"min 48"min 24"max 32"min 32"min			
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min			
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max			

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Measurement:	←10 min →1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 1 min 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No	I		
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: Accessible #:		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Steamboat Landing			
Location:			
Date: 10/8/19			
Evaluated By: Dom DeGuiseppi			

Priority !	5 - Parks			
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:		
Parking	Yes No			
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces
	number of accessible	Total #:	1 - 25	1
	spaces provided?	Accessible #:	26 - 50	2
	[208.2]		51 - 75	3
			76 - 100	4
			100+ see 2010 St	tandards 208.2
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:		

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: NA		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route					
5.9	Is the route stable, firm and slip-resistant? [302.1]	■ Yes No				
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: 10'	36"min			
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min			
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min			
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max			

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: 3%		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: 1.1%		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavilio	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No	I		
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: Accessible #:		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Sylvan Landing	
Location: SW 1st Street	
Date: 10/2/19	
Evaluated By: Dom DeGuiseppi	

Dui autus E. Daulsa					
Priority 5 - Parks					
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate number of accessible spaces provided? [208.2]	Yes ■No Total #: 3 Accessible #:	Total Spaces	Accessible Spaces	Additional parking but not marked
			1 - 25	1	
			26 - 50	2	markou
		0	51 - 75	3	
			76 - 100	4	
			100+ see 2010 St	andards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: NA		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1] Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from	Yes No Measurement:	36"min 48"min 424"max 32"min 32"min		
5.11	each other. If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:	
Curb	Ramps Yes No		
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No	
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement: 5.8%	1 1 1 2 min 1
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement: 1.2%	48 min 1

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement: 60"	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Measurement:	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:				
Bench	Benches Yes No					
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: 70" Yes No Yes No Measurement: 17"	48" min 30" min 20"- 24" 17"- 19"			
Dining	Tables Yes No					
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 2 Accessible #: 1				
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No				

Evaluated By: Dom DeGuiseppi	
Date: 10/2/19	
Location: SW 14th Ave	
Building: Sylvan Point Trail	

Priority !	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate number of accessible spaces provided? [208.2]	Yes No Total #: Accessible #:	Total Spaces 1 - 25 26 - 50 51 - 75 76 - 100 100+ see 2010 St	Accessible Spaces 1 2 3 4 andards 208.2	Dirt lot
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement:	36"min 48"min 48"max		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:			
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:			
Curb F	Curb Ramps Yes No				
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No			
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1		
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1		

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 12 min — 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are components that can be			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No	I		
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: Accessible #:		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Veteran's Memorial Park	
Location:	
Date: 10/8/19	
Evaluated By: Dom DeGuiseppi	

Priority 5	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	Grass and gravel lot, no paved
	number of accessible	Total #:	1 - 25	1	parking
	spaces provided?	Accessible #:	26 - 50	2	
	[208.2]	NA	51 - 75	3	
			76 - 100	4	
			100+ see 2010 St	tandards 208.2	
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior	Accessible Route			
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No		
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: 9'	36"min	
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min	
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: NA	36"min 60"min	
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max	

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: .5%		
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement: 1.4%		
Curb F	Ramps Yes No			
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1	
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Measurement:	10 min ———————————————————————————————————	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 1 min 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavilio			
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: NA	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: 70" Yes No Yes No Measurement: 17"	48" min 30" min 20"- 24" 17"- 19"	
<u> </u>				
	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 21 Accessible #: 5		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Wilcox Park
Location:
Date: 10/9/19
Evaluated By: Dom DeGuiseppi

Priority	5 - Parks				
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:			
Parking	Yes No				
5.2	If parking is provided for the public, are an adequate number of accessible spaces provided? [208.2]	Yes No Total #: Accessible #:	Total Spaces 1 - 25 26 - 50 51 - 75 76 - 100 100+ see 2010 Si	Accessible Spaces 1 2 3 4 tandards 208.2	Gravel Lot
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:			

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement:		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement:	36"min 48"min 48"max		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:	
Curb	Ramps Yes No		
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes ■ No	
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	12 min 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	Notes: 1. A play component is an element designed to generate play, socialization and learning. 2. Ground level play components are			
	2. Ground level play			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	
Pavili	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Bench	es Yes No			
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" min 17"- 19"	
Dining	Tables Yes No			
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 2 Accessible #: 0		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		

Building: Willow Park	
Location: Willow Lane	
Date: 10/1/19	
Evaluated By: Dom DeGuiseppi	

Priority	Priority 5 - Parks					
5.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes No If yes, location of route:				
Parking	Yes No					
5.2	If parking is provided for the public, are an adequate	Yes No	Total Spaces	Accessible Spaces	Street parking	
	number of accessible	Total #:	1 - 25	1		
	spaces provided?	Accessible #:	26 - 50	2		
	[208.2]		51 - 75	3		
			76 - 100	4		
			100+ see 2010 St	tandards 208.2		
5.3	Are accessible spaces at least 8 feet wide with an access aisle at least 8 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements;	Yes No Measurement:				

	some specify that each space have its own aisle.			
5.4	Are the access aisles marked with signage and surface painting so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	
5.5	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: NA		
5.6	Do the access aisles adjoin an accessible route? [502.3]	Yes No		
5.7	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches and not greater than 66 inches above the ground? [502.6]	Yes No Yes No Measurement:	60"min	
5.8	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1]	Yes No		

Exterior A	Exterior Accessible Route				
5.9	Is the route stable, firm and slip-resistant? [302.1]	Yes No			
5.10	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement:	36"min 48"min 48"max		
	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min		
5.11	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min		
5.12	If there are grates or openings on the route, are the openings no larger than ½ inches?	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	1/2" max		

5.13	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:			
5.14	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:			
Curb F	Curb Ramps Yes No				
5.15	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No			
5.16	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	12 min 1		
5.17	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1		

5.18	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	
5.19	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4]	Yes No Measurement:	36"min	
	If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No	10 min 1	
5.20	If the landing at the top is less than 36 inches long, are there curb ramp flares?	Yes No	1 1 min 1	
	Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Measurement:		
Acces	sible Play Components Yes	No		
5.21	Ground Level Play Components Is there an accessible route to at least one of each type of ground level play component?	Yes No		
	 A play component is an element designed to generate play, socialization and learning. Ground level play components are components that can be approached and exited at 			

	ground level. Examples include rockers, swings, diggers and stand-alone slides.		
5.22	Elevated Play Components Are there any accessible elevated play components? If so, is there an accessible route to the components?	Yes No	
5.23	Is the vertical clearance of the accessible route at least 80 inches above the ground surface? Note: Objects below 80 inches may not protrude into the accessible route.	Yes No	NA
Pavilio	on Yes No		
5.24	Is there an accessible route that is stable, firm and slip-resistant? [302.1]	Yes No	
5.25	Is the route at least 36 inches wide? [403.5.1]	Yes No	
5.26	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:	

5.27	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		
Benches Yes No				
5.28	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall? Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement: Yes No Measurement: Yes No Yes No Measurement:	48" min 30" min 20"- 24" min 17"- 19"	
Dining Tables Yes No				
5.28	Are at least 5 percent, but not less than one, of the dining surfaces for the seating and standing spaces accessible?	Yes No Total #: 2 Accessible #: 1		
	Is/are the accessible space(s) distributed throughout the facility and located on an accessible route?	Yes No		